

PIKA WARP Appliance for Linux / Asterisk®/Open Source

Datasheet

PIKA WARP Appliance is ideal for developers of all kinds looking for a small, low cost computer replacement to deploy telephony applications in the Small Office/Home Office (SOHO) and Small/Medium Enterprise (SME) markets. Completely customizable, it is compatible with VOIP phones as well as analog sets. Unlike your typical computer or appliance, PIKA has covered all your customer's traditional telephony requirements. Music on Hold (MOH) and Paging can be cumbersome to add to a data centric solution as is power failure transfer (PFT), but all are included in the PIKA appliance. The configuration of the appliance is modular and can include up to 9 ports of a combination of FXO/FXS/BRI/GSM plus VOIP stations and trunks. The appliance is designed to address businesses with up to 75 IP endpoints (trunks and stations) and 32 simultaneous calls.

Features & Benefits

- AMCC Power PC 440EP Embedded 533 MHz Processor
 - 1200 mips
 - Supports floating point and MMU (memory management unit)
- Internal flash 256 MB NAND (OS + apps) plus 4 MB NOR memory (uboot)
- Internal RAM 256 MB
- External removable 1 GB SD flash memory (no hard drive improves reliability)
 - for additional voice mail prompts / storage
 - back-up of configuration files and custom settings (facilitates unit replacement)
- 10/100BT Ethernet port
- One USB host port (v1.1)
- One FXS port with every unit
- Optional Expansion Modules (max 2): 4-port FXS station, 4-port FXO trunk, 2-port/4 channel BRI, 2-port GSM
- Each 4-port analog module also contains a power failure transfer jack (RJ-11)
- Audio in, Audio out jacks for music-on-hold and paging functions
- 40 character (2 x 20) LCD backlit display with scroll button (API controlled) inverts for wall mounting
- Power LED
- Reset function remotely controlled
- External brick-format universal power supply with country variant cords
- Surface standalone/stackable or wall mountable to accommodate any space requirements
- Customizable look so you can promote your brand!
- Dynamic thermal management (Fan)
- RS232 programming port



Software

Full suite of PIKA voice processing applications	tone detection and generation play/record VoIP conferencing echo cancellation
Pre-loaded with Linux OS, drivers and tools	2.6.x Linux kernel (stripped down PIKA version)
SSH (remote access)	Dropbear
Asterisk and Asterisk GUI	1.4.x
Database, web server, web language, common tools	Busybox 1.8.2 (binaries linux tools such as ssh, wget) SQLite3 (database) Httpd (webserver) PHP5 with support for SQLite, XML, PDO, etc. NTP, DHCP (client), TFTP (server and client), VLAN, DNS
Ability to add any software package that your application requires	
PIKA Warp Community for 3rd party apps	www.pikawarp.org

Technical Specifications

Physical Properties

Dimensions (Metric)	234mm W x 169mm D x 55mm H
Dimensions (Imperial)	9.25" W x 6.65" D x 2.18"H

Power Requirements

Input Voltage	AC 110V-240V (50-60 Hz)
Max Input Power	25W

Environment Requirements

Operating Temperature	0 °C to +40 °C
Storage Temperature	-20 °C to +85 °C
Humidity, Non-condensing	5% to 95%
Mean Time Between Failure (MTBF)	Base board with no modules = 30.6 years Base board with 2 modules (FXO/FXS) = 19.1 years Power Supply = 20.44 years

Telephony Interfaces

Standard station ports	1 FXS
Expansion Modules	2
Expansion Module Types	4 FXS/station (+PFT), 4 FXO/trunk (+PFT), 2 port/4 channel BRI /2 port GSM

21
years STRONG

FXO AC Impedance (in audio band)

Off-Hook	programmable
On-Hook Metallic (Tip to Ring)	>300 k ohms
Return Loss	>26.8 dB

FXO DC Current

Loop Current Range	13 - 110 mA
--------------------	-------------

FXO DC Resistance

Longitudinal (tip to ground, ring to ground)	>9.8 M ohms
On-Hook Metallic (Tip to Ring)	>6.5 M ohms
Off-Hook Metallic (Tip to Ring)	310 ohms @ 20mA 117 ohms @ 100 mA

FXS AC Impedance (in audio band)

Off-Hook	600 ohms or TBR21 complex impedance
Return Loss	>30 dB

FXS DC Feed

Open Loop Voltage	48V
Constant Loop Current	20 mA
Max Loop Length**	4kft

FXS Ringer Equivalence Number Supported

REN	1
-----	---

Regulatory Approvals

North American telecoms and safety	(FCC/DOC/UL/CSA)
European Union	(CE)
RoHS Compliant	
Others upon request	

Technical Support

Technical Support Specialists trained on Asterisk®
Support methods available to suit your needs: onsite assistance, email, phone, forum

PIKA Custom Engineering

Team of highly skilled application design engineers
Custom designed features and media processing applications
Access to testing facilities

21 STRONG
years



About PIKA Technologies Inc.

PIKA Technologies for over 21 years has been providing developers with the tools they need to build advanced voice and fax applications like IP PBX, fax broadcast and self-service IVR. As the technology landscape has changed, so too has PIKA, building out its product offering so its customers can choose the right tool set for their applications. Whether building applications using DSP board-based media processing, host-based solutions, or OPEN Source platforms such as Asterisk, trixbox, or FreeSWITCH, whether your application requires telephony boards or appliances, application developers of all kinds turn to PIKA for their development tools.

More Info

For detailed technical specifications go to www.pikatechnologies.com.

© Copyright PIKA Technologies Inc., 2009. All rights reserved. Printed in Canada. PIKA is a registered trademark and PIKA MonteCarlo, is a trademark of PIKA Technologies Inc. trixbox is a register trademark of Fonality Inc. Asterisk® is a registered trademark of Digium Inc.

No part of this publication may be reproduced, stored in a retrieval system or transmitted in any form or by any means, without the express written permission of PIKA Technologies Inc. This document is provided to you for informational purposes only and is believed to be accurate as of the date of its publication, and is subject to change without notice. PIKA Technologies Inc. assumes no responsibility for any errors or omissions in this document and shall have no obligation to you as a result of having made this document available to you or based upon the information it contains..



535 Legget Drive, Suite 400, Ottawa, Ontario, Canada, K2K 3B8 Tel: 613-591-1555 Fax: 613-591-9295

Visit www.pikatechnologies.com Email: sales@pikatech.com

© Copyright PIKA Technologies Inc., 2009. All rights reserved. No part of this publication may be reproduced, stored in a retrieval system or transmitted in any form or by any means, without the express written permission of PIKA Technologies Inc.

This document is provided to you for informational purposes only and is believed to be accurate as of the date of its publication, and is subject to change without notice. PIKA Technologies Inc. assumes no responsibility for any errors or omissions in this document and shall have no obligation to you as a result of having made this document available to you or based upon the information it contains.

PIKA is a registered trademark, and AllOnHost is a trademark of PIKA Technologies Inc.

updated Jan 20, 2009

21 STRONG
years

PIKA TECHNOLOGIES INC.